



Canopy Light- III

Fuel Pump Canopy Luminaires / Exterior Fixtures & Retrofit Kits





Model Number	CP-100W-1111-1601 (CM)	CP-130W-1111-1601 (CM)	CP-150W-3111-1601 (CM)
	CP-100W-1112-1601 (TRM)	CP-130W-1112-1601 (TRM)	CP-150W-3112-1601 (TRM)
PIC Code	C-100	C-130	C-150
Wattage	100W	130W	150W
Lumen	11,500 LM	14,900 LM	17,000 LM
Power Supply	Meanwell	Meanwell	Meanwell: CLG
Dimension	10.6" x 10.6" x 3.5"		15.0" x 15.0" x 3.1"
Voltage	AC100~277V 50/60Hz		1601= AC100~277V 50/60Hz 1602= AC 200~400V

COMMON SPECS:

Lumen Efficacy	110~115 LM/W	CCT	4,000K, 5,000K, 5,700K
Viewing Angle	110°	IP Grade	IP65

Canopy Light- III

Fuel Pump Canopy Luminaires / Exterior Fixtures & Retrofit Kits



Model Number	CP-45W-2111-1601 (CM)	CP-75W-2111-1601 (CM)
	CP-45W-2112-1601 (TRM)	CP-75W-2112-1601 (TRM)
PIC Code	C-045	C-075
Wattage	45W	75W
Lumen	5,000 LM	8,600 LM

COMMON SPECS:

Dimension	10.6" x 10.6" x 3.5"	LED Brand	LUMILEDS
Voltage	AC100~277V 50/60Hz	CCT	4,000K, 5,000K, 5,700K
Power Supply	Song Sheng	IP Grade	IP65
Lumen Efficacy	110~115 LM/W	Housing	Aluminum
Viewing Angle	110°		

Model NO.	PIC Code	Watts	MSRP	PG&E Code
CP-45W-211X-1601	C-045	45W	\$110.00	LT015
CP-75W-211X-1601	C-075	75W	\$140.00	LT013
CP-100W-111X-1601	C-100	100W	\$240.00	LT013
CP-130W-111X-1601	C-130	130W	\$260.00	LT012
CP-150W-311X-1601	C-150	150W	\$270.00	LT011

How to Order:

CP	100W	111	X	1601	5700k
Product	Watts	211: 45W, 75W 111: 100W, 130W 311: 150W	Mounting 1 CM 2 TRM	1601= AC100~277V 1602= AC200~480V	CCT

For Volume Discount, and Utility Rebate Program, please call us.