

LED Wall Pack Light Instruction

Application :

Available in tunnel (except for motor vehicle tunnel), workshop, warehouse, factory, house, building exterior, etc.

Caution :

1. Can not use the electric generator to test the LED lamp.
2. Please abide by related country, regional and local law and regulations when install this fixture.
3. Please don't install the fixture when raining to lower the risk of electric shock and avoid the failure.

Note :

1. To avoid possibility of electrical shock or fire, the installation personnel must have professional electric knowledge.
2. Please wear gloves to avoid injury before installation.
3. If any smoke or spark of the wire happened, please turn off the power immediately and notify relevant personnel.
4. This fixture is available in outdoor usage, but the distance from fixture to ground should be more than 2m.

Figure 5 applies to installation method I and II, Figure 9 only applies to installation method II .

Installation I:

1. Rotate 3 mounting kits to the proper angle. (Figure 1)




Figure 1

2. Put the fixture on the wall, make three marks according to 3 mounting kits, then drill 3 holes for them. (Figure 2)




Figure 2

3. Get rubber plugs into the holes, match 3 mounting kits to the rubber plugs, then fix the fixture on the wall by screws. (Figure 3)




Figure 3




Figure 4

4. Make wiring connections per "Electrical Connections" section and make sure the good wire protection.




Figure 5

Installation II:

1. Take apart the PC cover and fixture housing. (Figure 6)




Figure 6

2. Put the fixture on the wall, drill 3 holes to get through the wall. (Figure 7)




Figure 7

3. Get expansion screws into the holes, match the fixture to the bolts, then fix the fixture on the wall by screws, lastly get the PC cover and fixture housing back together. (Figure 8)




Figure 8

4. Make wiring connections per "Electrical Connections" section and make sure the good wire protection.




Figure 9

Standard wire:

L/live wire:Black\Brown;
N/null wire:White\Blue;
Ground wire:Green\Yellow-green.

Warning/Avertissement:

MIN 75 °C SUPPLY CONDUCTOR

THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED

LES FILS D'ALIMENTATION 75 °C MIN

CE PRODUIT DOIT ÊTRE INSTALLÉ SELON LE CODE D'INSTALLATION PERTINENT, PAR UNE PERSONNE QUI CONNAÎT BIEN LE PRODUIT ET SON FONCTIONNEMENT AINSI QUE LES RISQUES INHÉRENTS.